



确认后请签字并回传:

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSPARENT/POSITIVE
- 4.OPERATING TEMP: -10°C--+60°C
- 5.STORAGE TEMP: -20°C--+70°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 8.CONTROLLER: KS0108B
- 9.BACKLIGHT TYPE:LED(YELLOW-GREEN;5.0DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

1	2	3	4	5	6	7	8	9	10	11
VSS	VDD	V0	RS	R/W	E	RET	D0	D1	D2	D3
D4	D5	D6	D7	CS1	CS2	CS3	CS4	VOUT	ELK	ELA

深圳市耀宇科技有限公司 SHENZHENG YAOUYU TECHNOLOGY CO.LTD		
绘图:	绘图编号: YMSC-G128128C01SYMDC-1	单位: mm
审核:	客户编号: YMSC-G128128C01SYMDC	日期:
批准:	图纸版号: C-1	页数: