



PINNO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
SIGNAL	NC	V0	V1	V2	V3	V4	VR	OSC1	INTRS	VEXT	REF	VOUT_IN	VOUT_OUT	VSS	VDD
PINNO.	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
SIGNAL	D7	D6	D5	D4	D3	D2	D1	D0	E_RD	RW_WR	A0	RST	CSB	PS1	NC

NOTES:

- 1.DISPLAY TYPE: FSTN/FILTER UV
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C ~ +60°C
- 5.STORAGE TEMP: -20°C ~ +70°C
- 6.LOGIC VOLTAGE: VDD=3.0V
- 7.LCD DRIVING VOLTAGE:VOP=12.0V
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.DRIVE IC: ST7541

		深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD			
DRAW NO.	YMFG-G128128GDPNNN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
TOLERANCES UNLESS:±0.3					
REV.	DESCRIPTION	DATE			