



1	2	3	4	5	6	7	8	9
V6	V5	V4	V3	V2	C2P	C2N	C1N	C1P
10	11	12	13	14	15	16	17	18
C3N	VEE	VSS	VDD	SDA	SDK	D/C	/CS1	/RST

- NOTES:
- 1.DISPLAY TYPE:STN/YELLOW-GREEN
 - 2.VIEWING ANGLE:6:00
 - 3.POLARIZER MODE:TRANSMISSIVE/POSITIVE
 - 4.OPERATING TEMP:-20°C~+70°C
 - 5.STORAGE TEMP:-30°C~+80°C
 - 6.LOGIC VOLTAGE: VDD=3.0V
 - 7.LCD DRIVER VOLTAGE: Vlcd=9.0V
 - 8.DRIVE METHOD:1/64DUTY,1/9BIAS
 - 9.DRIVE IC:SSD1815
 - 10.BACKLIGHT TYPE:LED/WHITE



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO., LTD.

REV.	DESCRIPTION	DATE	DRAW NO.	YM12864P-7	DRAWN	ME CHECKED	EE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
				TOLERANCES UNLESS:				