



NOTES:

- | | |
|---------------------------|------------------------|
| 1. DISPLAY TYPE: | FSTN |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. OPERATING TEMP: | -20°C~+70°C |
| 5. STORAGE TEMP: | -30°C~+80°C |
| 6. LOGIC VOLTAGE: | 3.2V |
| 7. LCD OPERATION VOLTAGE: | 16.0V |
| 8. DRIVE METHOD: | 1/160DUTY 1/13BIAS |
| 9. DRIVER IC: | ST7529-F1 |
| 10. BACKLIGHT: | LED(WHITE, SIDE) |

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
VDD	RST	WR	RD	CS	RS	D0	D1	D2	D3	D4	D5	D6	D7	K_EN	NC	VEE	VSS

 深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD					
DRAW NO.	YMFT-G160160B-2DPSWSN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1		
 TOLERANCE UNLESS:±0.3					