



NOTES:

- 3.0±0.3
- +1.0±0.1
- 5.0±0.3
- 2.0±0.3

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSPARENTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+60°C
- 5.STORAGE TEMP: -20°C--+70°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 8.CONTROLLER: T6963C
- 9.BACKLIGHT TYPE:LED(YELLOW-GREEN;4.2DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

1	FG
2	VSS
3	VDD
4	V0
5	WR
6	RD
7	CE
8	C/D
9	RSTB
10	DB0
11	DB1
12	DB2
13	DB3
14	DB4
15	DB5
16	DB6
17	DB7
18	FS
19	A
20	K

深圳市耀宇科技有限公司		
SHENZHENG YAORYU TECHNOLOGY CO.,LTD		
绘图:	绘图编号: YNSP-G12864PDYTYNDG-1	单位: mm
审核:	客户编号: YNSP-G12864PDYTYND	日期:
批准:	图纸版号: C-1	页数: