



**DOT FOR DETAIL**  
**SCALE 10:1**

**NOTES:**

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
- 4.OPERATING TEMP: -20°C ~ +70°C
- 5.STORAGE TEMP: -30°C ~ +80°C
- 6.LOGIC VOLTAGE: VDD=5.0V
- 7.LCD DRIVER VOLTAGE: Vop=18.5V
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.DRIVE IC: T6963C
- 10.BACKLIGHT TYPE: WHITE LED BACKLIGHT

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FG	VSS	VDD	V0	/WR	/RD	/CE	C/D	/RST	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7
18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
FS	VEE	A	K	NC	ED	CDATA	FR	LP	CP	NC	VDD	VSS	V0	VEE	A	K



深圳市耀宇科技有限公司  
SHENZHEN YAO YU TECHNOLOGY CO., LTD.

DRAW NO.	YMS-P-G240128ADBSWD	DRAWN/ME	CHECKED	EE	CHECKED	APPROVED
UNIT:mm	PAGE:1/1 VER:A SCALE:1/1					
	TOLERANCE UNLESS:±0.2					