



1	2	3	4	5	6	7	8	9	10	11	12	13	14
CS1B/RES	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	VDD	
15	16	17	18	19	20	21	22	23	24	25	26	27	
VSS	VOUT	C4+	C3+	C1-	C1+	C2+	C2-	V1	V2	V3	V4	V0	

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE: TRANSPARENT/POSITIVE
- 4.OPERATING TEMP: 0°C~+50°C
- 5.STORAGE TEMP: -10°C~+60°C
- 6.LOGIC VOLTAGE: VDD=3.3V
- 7.LCD DRIVER VOLTAGE: Vop=8.5V
- 8.DRIVE METHOD: 1/6SDUY,1/9BIAS
- 9.DRIVE IC: S6B0724
- 10.BACKLIGHT TYPE: _____

深 圳 市 耀 宇 科 技 有 限 公 司
SHENZHEN YAO YU TECHNOLOGY CO., LTD.

REV.	DESCRIPTION	DATE	DRAW NO.	MGS-G12864P-21DMMN	DRAWN	ME CHECKED	DEE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
				TOLERANCES UNLESS:				