



1	2	3	4	5	6	7	8	9	10	11	12
P_C	/RST	VSS	VSS	VDD	NC	D/I	R/W	/CS1	DB0	DB1	DB2
13	14	15	16	17	18	19	20	21	22	23	
DB3	DB4	DB5	DB6	DB7	E	NC	/CS2	NC	LED+	LED-	

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW-GREEN
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE: TRANSPARENT/POSITIVE
 - 4.OPERATING TEMP: -20°C~+70°C
 - 5.STORAGE TEMP: -30°C~+80°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=8.8V
 - 8.DRIVE METHOD: 1/64DUTY,1/9BIAS
 - 9.DRIVE IC: KS0107,KS0108
 - 10.BACKLIGHT TYPE: YELLOW-GREEN



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO., LTD.

REV.	DESCRIPTION	DATE	DRAW NO.	YMSC-G12864X-20YL YSD	DRAWN	ME CHECKED	EE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
				TOLERANCES UNLESS:				