


PIN	NAME
1	VCC
2	GND
3	CS1B
4	CS2
5	RESET
6	RS
7	R/W
8	ERD
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7
17	MI
18	P/S

PIN1	Y2
PIN2	X1
PIN3	Y1
PIN4	X2



NOTES:

- 1.DISPLAY TYPE: FSTN
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C ~ +70°C
- 5.STORAGE TEMP: -30°C ~ +80°C
- 6.LOGIC VOLTAGE: VDD=3.0V
- 7.LCD DRIVER VOLTAGE: Vop=9.0V
- 8.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 9.DRIVE IC: KS0713
- 10.BACKLIGHT TYPE: WHITE EDGE LED



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO., LTD

REV.	DESCRIPTION	DATE	DRAW NO. YMFT-G12864T-5DPWSWN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: G	SCALE:1/1	
				TOLERANCES UNLESS:±0.1			