



NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/NEGATIVE
- 4.OPERATING TEMP: -20°C--+70°C
- 5.STORAGE TEMP: -30°C--+80°C
- 6.LOGIC SUPPLY VOLTAGE: VDD=5.0V
- 7.LCD DRIVE VOLTAGE: VOP=5.0V
- 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 8.CONTROLLER: ST7920
- 9.BACKLIGHT TYPE: LED(WHITE)

1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	RS	R/W	E	D0	D1	D2	D3
11	12	13	14	15	16	17	18	19	20
D4	D5	D6	D7	PSB	NC	/RET	VOUT	ELA	ELK



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO., LTD

DRAW NO.	YMSC-G12864Y-2DBSWSD	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1		
⊕	TOLERANCE UNLESS:±0.2				

REV.	DESCRIPTION	DATE