


NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSELECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+50°C
- 5.STORAGE TEMP: -20°C--+60°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 8.DRIVE: T69693C
- 9.BACKLIGHT TYPE:LED(YELLOW-GREEN;4.2±0.1DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

1	FG	12	DB0
2	VSS	13	DB1
3	VDD	14	DB2
4	V0	15	DB3
5	VEE	16	DB4
6	/WR	17	DB5
7	/RD	18	DB6
8	/CE	19	DB7
9	C/D	20	NC
10	HALT	21	A
11	RESET	22	K



深圳市耀宇科技有限公司
SHENZHEN YAOYU TECHNOLOGY CO.,LTD

绘图:

绘图编号: YKSP-G160128ADY1YMD-1

单位: mm

审核:

客户编号: YKSP-G160128ADY1YMD

日期:

批准:

图纸版本号: G-1

页数:

