



**NOTES:**

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C ~ +70°C
- 5.STORAGE TEMP: -30°C ~ +80°C
- 6.LOGIC VOLTAGE: VDD=5.0V
- 7.LCD DRIVER VOLTAGE: Vop=18.2
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.CONTROLLER IC: T6963C
- 10.BACKLIGHT TYPE: IF=160mA YELLOW-GREEN S-LED

1	2	3	4	5	6	7	8	9	10
FG	VSS	VDD	V0	/WR	/RD	/CE	C/D	RST	DB0
11	12	13	14	15	16	17	18	19	20
DB1	DB2	DB3	DB4	DB5	DB6	DB7	FS	LEDA	LEDK

 深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD					
DRAW NO.	YMSP-G240128A-13DYSYSD	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1		
	TOLERANCE UNLESS:±0.3				