



确认后请签字并回传:

NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
- 4.OPERATING TEMP: -10°C---+60°C
- 5.STORAGE TEMP: -20°C---+70°C
- 6.VDD: +5.0V
- 7.LCD OPERATING VOLTAGE: 15.0V
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.DRIVE: T6963C
- 10.BACKLIGHT TYPE: LED(WHITE;5.0DCV)
- 11.ALL UNMARKED TOLERANCES: ±0.30mm

1	2	3	4	5	6	7	8	9	10	11
FG	GND	VDD	VLCD	WR	RD	CE	C/D	NC	RES	DB0
12	13	14	15	16	17	18	19	20	21	22
DB1	DB2	DB3	DB4	DB5	DB6	DB7	FS	VDUT	A	K

深圳市耀宇科技有限公司
SHENZHENG YAoyu TECHNOLOGY CO.,LTD

绘图: 绘图编号: YMSP-C240128K-2DBSWMDC-2 单位: mm

审核: 客户编号: YMSP-C240128K-2DBSWMDC 日期:

批准: 图纸版号: G-2 页数: