



- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW -GREEN
 - 2.VIEWING DIRECTION: 6:00
 - 3.POLARIZER MODE: TRANSPARENT/POSITIVE
 - 4.OPERATING TEMP: -10°C---+60°C
 - 5.STORAGE TEMP: -20°C---+70°C
 - 6.LCD OPERATING VOLTAGE:18.5V
 - 7.DRIVE METHOD: 1/128 DUTY 1/12BIAS
 - 8.CONTROLLER: T6963C
 - 9.BACKLIGHT: LED(YELLOW -GREEN),4.2DCV)
 - 10.ALL UNMARKED TOLERANCES:±0.3mm
 - 11.BEZEL THICKNESS: 0.6mm) IS TO BE PAINTED BLACK

1	FG	11	DB1
2	VSS	12	DB2
3	VDD	13	DB3
4	V0	14	DB4
5	/WR	15	DB5
6	/RD	16	DB6
7	/CE	17	DB7
8	C/D	18	FS
9	RESET	19	A
10	DB0	20	K

耀宇科技有限公司

DRAWN BY:		TITLE: YM240128K	
CHECKED BY:		SCALE:	
APPROVED BY:		UNIT: mm	
CONFIRMED BY:		DWG NAME: YM240128KG-1 SHEET NO: 1 OF 1	