


- NOTES:
- 1. DISPLAY TYPE: FSTN
 - 2. VIEWING DIRECTION: 6:00
 - 3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
 - 4. OPERATING TEMP: -20°C~+70°C
 - 5. STORAGE TEMP: -30°C~+80°C
 - 6. LOGIC VOLTAGE: 5V
 - 7. LCD OPERATION VOLTAGE: 19.6V
 - 8. DRIVE METHOD: 1/16DUTY 1/13BIAS
 - 9. DRIVER IC: RA8835
 - 10. BACKLIGHT: LED(WHITE)

1	RESET	11	DB5
2	RD	12	DB6
3	WR	13	DB7
4	CS	14	VDD
5	A0	15	VSS
6	DB0	16	VLCD
7	DB1	17	VADJ
8	DB2	18	LED ON
9	DB3	19	LED A
10	DB4	20	LED K

 深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD							
DRAW NO.	YMFT-G240160A-3DPSWD			DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1				
 TOLERANCE UNLESS:±0.3							