



240X64 DOTS

1	FG	12	DB1
2	VSS	13	DB2
3	VDD	14	DB3
4	V0	15	DB4
5	/WR	16	DB5
6	/RD	17	DB6
7	/CE	18	DB7
8	C/D	19	FS
9	NC	20	VEE
10	RESET	21	K
11	DB0	22	Ak(+5.0)

- NOTES:
- 1.DISPLAY TYPE: STN/BLUE
 - 2.VIEWING DIRECTION: 6:00
 - 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
 - 4.OPERATING TEMP: -10°C--+60°C
 - 5.STORAGE TEMP: -20°C--+70°C
 - 6.VDD: +5.0V
 - 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
 - 8.DRIVE: T6963C
 - 9.BACKLIGHT TYPE: LED(WHITE;5.0VDC)
 - 10.ALL UNMARKED TOLERANCES: ±0.30mm

深圳市耀宇科技有限公司 SHENZHENG YAORYU TECHNOLOGY CO.LTD		
绘图:	绘图编号: YMSP-G24064CDBS/WDC-1	单位: mm
审核:	客户编号: YMSP-G24064CDBS/WDC	日期:
批准:	图纸版本号: G-1	页数: