



CON1

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

CON2

1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	/WR	/RD	/CS	A0	RST	D0	D1
11	12	13	14	15	16	17	18	19	20
D2	D3	D4	D5	D6	D7	NC	VDUT	NC	NC

NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSPARENT/NEGATIVE
- 4.OPERATING TEMP: 0°C---+50°C
- 5.STORAGE TEMP: -10°C---+60°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/240DUTY 1/17BIAS
- 8.CONTROLLER: SED1335F0A
- 9.BACKLIGHT TYPE: CCFL(WHITE)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

深圳市耀宇科技有限公司
SHENZHEN YAOYU TECHNOLOGY CO.,LTD

绘图:	绘图编号: YASP-G320240D02C/WND-1E-1	单位:	mm
审核:	客户编号: YASP-G320240D02C/WND-1	日期:	
批准:	图纸版本号: G-1	页数:	