



PN	SIGNAL
1	/CS1
2	/RES
3	A0
4	WR
5	RD
6	DD
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	VDD
15	VSS
16	VOUT
17	CSW
18	C1P
19	C1N
20	CSN
21	C1P
22	V12
23	V13
24	V14
25	V15
26	V16
27	V17
28	VSS
29	RES
30	VDD

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW-GREEN
  - 2.VIEWING ANGLE: 6:00
  - 3.POLARIZER MODE:TRANSMISSIVE/POSITIVE
  - 4.OPERATING TEMP: -20°C ~ +60°C
  - 5.STORAGE TEMP: -30°C ~ +70°C
  - 6.LOGIC VOLTAGE: VDD=3.0V
  - 7.LCD DRIVER VOLTAGE: Vop=9.0V
  - 8.DRIVE METHOD: 1/64DUTY 1/9BIAS
  - 9.DRIVE IC: SSD18158Z
  - 10.BACKLIGHT TYPE: YELLOW-GREEN EDGE LED

DOTS SCALE:20/1



深圳耀宇科技有限公司  
SHENZHEN YAO YU TECHNOLOGY CO., LTD

DRAW NO. YMSG-012864P-12DYWSN	UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1	DRAWN	WE CHECKED	EE CHECKED	APPROVED
DESCRIPTION	DATE							
REV.								