



Dot: 128*64

SCALE:10/1

PN NO.	1	2	3	4	5	6	7	8	9	10
NAME	/CSA	/CSB	VSS	VDD	V0	RS	R/W	E	DB0	DB1
PN NO.	11	12	13	14	15	16	17	18	19	20
NAME	DB2	DB3	DB4	DB5	DB6	DB7	/RST	V0UT	A	K

- NOTES:
- 1.DISPLAY TYPE: FSTN
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE: TRANSPARENTIVE/POSITIVE
 - 4.OPERATING TEMP: -25°C~~+75°C
 - 5.STORAGE TEMP: -35°C~~+80°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: ---
 - 8.DRIVE METHOD: 1/64DUTY,1/9BIAS
 - 9.DRIVE IC: KS0108
 - 10.BACKLIGHT TYPE: SIDE LED BACKLIGHT

 深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD.				
DRAW NO.	YMFC-G12864C-3DPSWSD	DRAWN	ME CHECKED/EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1	
	TOLERANCES UNLESS: ±0.2		YNN	