



↑  
VIEWING DIRECTION

**SPECIFICATIONS**

**DISPLAY MODE :** FSTN , POSITIVE MODE  
**DRIVE CONDITION :** 1/105 DUTY , 1/11 BIAS  
**VIEWING DIRECTION :** 6 O'CLOCK  
**OPERATING TEMP :** -10°C TO +60°C  
**STORAGE TEMP :** -20°C TO +70°C  
**OPERATING VOLTAGE:** 12.5 V  
**FRONT POLARIZER :** TRANSMISSIVE,ADHESIVE  
**BACK POLARIZER :** TRANSFLECTIVE,ADHESIVE  
**CUSTOMER NO.:** 160105  
**CONNECTORS :** COG (IC:S6B0719)

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14
SYMBOL	CS2B	RESETB	RS	WR	RD	D0	D1	D2	D3	D4	D5	D6	D7	VDD
PIN	15	16	17	18	19	20	21	22	23	24	25	26	27	28
SYMBOL	VSS	VOUT	C5+	C3+	C1-	C1+	C2+	C2-	C4+	V4	V3	V2	V1	V0

 深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO.,LTD							
DRAW NO.	YMFG-G160105CDPNNWN			DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/3	VER. A	SCALE:1/1				
 TOLERANCE UNLESS:±0.2							