



SCALE TO 10/1

Unmarked tolerance: x.xx±0.20 WITH EL B/L WITH LED B/L
 x.x±0.3 WITHOUT B/L

Parallel Interface:

PIN NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
SIGNAL	VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BL+	BL-

Serial Interface:

PIN NO.	17	18	19	20	21	22	23	24
SIGNAL	VSS	VDD	VO	CLK	SID	CS	BL+	BL-

- NOTES:
- 1.DISPLAY TYPE: Positive Type, Negative Type
 - 2.VIEWING ANGLE: 6:00, 12:00
 - 3.POLARIZER MODE: Transmissive/Reflective/Transflective
 - 4.OPERATING TEMP: -10°C~+50°C
 - 5.STORAGE TEMP: -20°C~+60°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vlcd=4.7V
 - 8.DRIVE METHOD: 1/32DUTY , 1/5BIAS
 - 9.DRIVE IC: ST7920(chinese character)
 - 10.BACKLIGHT TYPE: EL:Green,Blue-Green,Blue,White Without

		深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD.	
DRAW NO.	YM-12232F	DRAWN	
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1
TOLERANCES UNLESS:±0.1		ME CHECKED	EE CHECKED
		APPROVED	