


NOTES:

- | | |
|---------------------------|------------------------|
| 1. DISPLAY TYPE: | STN/BLUE |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. OPERATING TEMP: | -10°C~+60°C |
| 5. STORAGE TEMP: | -20°C~+70°C |
| 6. LOGIC VOLTAGE: | 5V |
| 7. LCD OPERATION VOLTAGE: | 4.8V |
| 8. DRIVE METHOD: | 1/32DUTY 1/6BIAS |
| 9. DRIVER IC: | SED1520 |
| 10.BACKLIGHT: | LED(WHITE) |



1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	A0	NC	NC	E1	E2	R/W	DO
11	12	13	14	15	16	17	18	19	20
D1	D2	D3	D4	D5	D6	D7	RES	A	K



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO.,LTD

DRAW NO.	YMSC-C12232G-2DBSWWN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. C	SCALE:1/1		
	TOLERANCE UNLESS:±0.2				