


PIN ASSIGNMENT

|        |      |    |    |     |     |     |    |     |    |
|--------|------|----|----|-----|-----|-----|----|-----|----|
| PINNO. | 1    | 2  | 3  | 4   | 5   | 6   | 7  | 8   | 9  |
| SIGNAL | V4   | V1 | VO | VDD | FRM | VSS | LP | VSS | M  |
| PINNO. | 10   | 11 | 12 | 13  | 14  | 15  | 16 | 17  | 18 |
| SIGNAL | DISP | CP | V3 | V2  | D3  | D2  | D1 | D0  | NC |

DOTS SCALE:20/1



- NOTES:
- 1.DISPLAY TYPE: FSTN
  - 2.VIEWING ANGLE: 6:00
  - 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
  - 4.OPERATING TEMP: -20°C ~ +70°C
  - 5.STORAGE TEMP: -30°C ~ +80°C
  - 6.LOGIC VOLTAGE: VDD=3.3V
  - 7.LCD DRIVER VOLTAGE: Vop=21.5V
  - 8.DRIVE METHOD: 1/240DUTY 1/17BIAS
  - 9.DRIVE IC:IST3025、IST3026
  - 10.BACKLIGHT TYPE: WHITE LED BL
  - 11.FRAME: Stainless Steel Thickness=0.3MM



深圳市耀宇科技有限公司  
SHENZHEN YAO YU TECHNOLOGY CO., LTD

|      |             |             |      |          |                        |        |            |            |          |
|------|-------------|-------------|------|----------|------------------------|--------|------------|------------|----------|
| REV. | ADD THE DIM | DESCRIPTION | DATE | DRAW NO. | YMFG-G320240E-4DPSWSD  | DRAWN  | ME CHECKED | EE CHECKED | APPROVED |
|      |             |             |      | UNIT:mm  | PAGE:1/1               | VER: B | SCALE:1/1  |            |          |
|      |             |             |      |          | TOLERANCES UNLESS:±0.2 |        |            |            |          |