


CON1

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

CON2



NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSPARENT/NEGATIVE
- 4.OPERATING TEMP: 0°C---+50°C
- 5.STORAGE TEMP: -10°C---+60°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/240DUTY 1/17BIAS
- 8.CONTROLLER: WITHOUT
- 9.BACKLIGHT TYPE: CCFL(WHITE)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm

1	2	3	4	5	6	7	8	9	10
FRAME	LOAD	CP	M	V0	VDD	VSS	VEE	D0	D1
D2	D3	DISPFF	NC	NC	NC	NC	VOUT	NC	NC

深圳市耀宇科技有限公司  
SHENZHENG YAOUYU TECHNOLOGY CO.LTD



绘图:	绘图编号: YMSP-G320240BDC/MN-2G-1	单位: mm
审核:	客户编号: YMSP-G320240BDC/MN-2	日期:
批准:	图纸版本号: G-1	页数: