


SCALE: 10/1

| | | | | | |
|-----|-----|-----|------|-----|-----|
| 1 | 2 | 3 | 4 | 5 | 6 |
| VDD | VSS | V0 | /RET | E1 | E2 |
| 7 | 8 | 9 | 10 | 11 | 12 |
| R/W | RS | DB0 | DB1 | DB2 | DB3 |
| 13 | 14 | 15 | 16 | 17 | 18 |
| DB4 | DB5 | DB6 | DB7 | NC | NC |

- NOTES:
- 1.DISPLAY TYPE:STN,TN,HTN,FSTN
 - 2.VIEWING ANGLE:6:00,12:00
 - 3.POLARIZER MODE: TRANSMISSIVE,REFLECTIVE, TRANSFLECTIVE
 - 4.OPERATING TEMP: -20°C~+70°C
 - 5.STORAGE TEMP: -30°C~+80°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: VLCD=4.7V
 - 8.DRIVE METHOD:1/32DUTY,1/6BIAS
 - 9.DRIVE IC: SED1520
 - 10.BACKLIGHT TYPE:EL: GREEN,BLUE-GREEN,BLUE, WHITE, WITHOUT


 深 圳 市 耀 宇 科 技 有 限 公 司
 SHENZHEN YAO YU TECHNOLOGY CO., LTD.

| | | | | | |
|----------|-------------------------|--------|------------|------------|----------|
| DRAW NO. | YM12232A-4 | DRAWN | ME CHECKED | EE CHECKED | APPROVED |
| UNIT:mm | PAGE:1/1 | VER: A | SCALE:1/1 | | |
| | TOLERANCES UNLESS: ±0.2 | | | | |