



SCALE: 10/1

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW-GREEN
  - 2.VIEWING ANGLE: 6:00
  - 3.POLARIZER MODE: TRANSPARENT/POSITIVE
  - 4.OPERATING TEMP: -20°C~+70°C
  - 5.STORAGE TEMP: -30°C~+80°C
  - 6.LOGIC VOLTAGE: VDD=5.0V
  - 7.LCD DRIVER VOLTAGE: ---
  - 8.DRIVE METHOD: 1/32DUTY,1/5BIAS
  - 9.DRIVE IC: ST7920
  - 10.BACKLIGHT TYPE: LED(YELLOW-GREEN)

PIN NO.	1	2	3	4	5	6	7	8	9	10
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3
PIN NO.	11	12	13	14	15	16	17	18	19	20
NAME	DB4	DB5	DB6	DB7	PSB	NC	/RES	NC	K	A

  
 深 圳 市 耀 宇 科 技 有 限 公 司  
 SHENZHEN YAO YU TECHNOLOGY CO., LTD.

DRAW NO.	YMSC-G12864A-4DYLYSN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
	TOLERANCES UNLESS: ±0.3				