


- NOTES:
- 1.DISPLAY TYPE:
 - 2.VIEWING ANGLE:
 - 3.POLARIZER MODE:
 - 4.OPERATING TEMP:
 - 5.STORAGE TEMP:
 - 6.LOGIC VOLTAGE:
 - 7.LCD DRIVER VOLTAGE:
 - 8.DRIVE METHOD:
 - 9.DRIVE IC:
 - 10.BACKLIGHT TYPE:

FSTN
6:00
TRANSMISSIVE/POSITIVE
-20°C~~+70°C
-30°C~~+80°C
VDD=5.0V
Vop=12.5V
SCALE:10/1



1	2	3	4	5	6	7	8	9	10	11
VSS	VDD	V0	C/D	/RD	/WR	DB0	DB1	DB2	DB3	DB4
12	13	14	15	16	17	18	19	20	21	22
DB5	DB6	DB7	CE	/RST	VEE	MD	FS	NC	LED+	LED-

1/64DUTY,1/9BIAS
T6963C
LED/YELLOW-GREEN(+4.2VDC)

		深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD.	
		DRAW NO. YM24064X	DRAWN
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1
TOLERANCES UNLESS: ±0.2			