


PINNO.	1	2	3	4	5	6	7	8	9	10
SIGNAL	FG	VSS	VDD	VEE	/WR	/RD	/CE	C/D	/RES	DB0
PINNO.	11	12	13	14	15	16	17	18	19	20
SIGNAL	DB1	DB2	DB3	DB4	DB5	DB6	DB7	FS	A	K



DOTS SCALE:10/1

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW-GREEN
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
 - 4.OPERATING TEMP: -20°C ~ +50°C
 - 5.STORAGE TEMP: -20°C ~ +70°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=17.4V
 - 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
 - 9.DRIVE IC: T6963C+NT7086
 - 10.BACKLIGHT TYPE: YELLOW-GREEN LED



深圳市耀宇科技有限公司
SHENZHEN YAO YU TECHNOLOGY CO., LTD

REV.	DESCRIPTION	DATE	DRAW NO. YWSP-G128128B-1DLYWNG-1	DRAWN	ME CHECKED	EE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1	
			TOLERANCES UNLESS:±0.3				