



SCALE: 10/1

1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	RS	RW	E	DB0	DB1	DB2	DB3
11	12	13	14	15	16	17	18	19	20
DB4	DB5	DB6	DB7	CS1	CS2	/RES	VEE	A	K

- NOTES:
- 1.DISPLAY TYPE: STN/BLUE
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
 - 4.OPERATING TEMP: -40°C~~+80°C
 - 5.STORAGE TEMP: -40°C~~+90°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=10.5V
 - 8.DRIVE METHOD: 1/64DUTY,1/9BIAS
 - 9.DRIVE IC: KS0108B
 - 10.BACKLIGHT TYPE: LED/WHITE,3.0V,SIDE

 深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD					
DRAW NO.	YM5C-G12864J-7DBSWZD	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1		
TOLERANCE UNLESS:±0.2		 2010-11-27			