


- NOTES:
1. DISPLAY TYPE: **FSTN**
 2. VIEWING DIRECTION: **6: 00**
 3. POLARIZER MODE: **TRANSMISSIVE/POSITIVE**
 4. OPERATING TEMP: **-20°C~+70°C**
 5. STORAGE TEMP: **-30°C~+80°C**
 6. LCD OPERATION VOLTAGE: **17. 30**
 7. DRIVE METHOD: **1/160DUTY 1/14BIAS**
 8. DRIVER IC: **IST3225TA0&IST3226TA0**
 9. Interface bus mode: **4-bit parallel interface**
 10. Logic power supply voltage: **3. 3V**
 11. BACKLIGHT: **3. 3V, White**
 12. CONNECTOR: **FCFC CONNECTOR**



PIN3 FUNCTION:

21'	21
22'	22
23'	23
24'	24
25'	25
26'	26
27'	27
28'	28
29'	29
30'	30

PIN1 FUNCTION:

1	VSS
2	VDD
3	D0
4	D1
5	D2
6	D3
7	VFRAM
8	VM
9	CL1
10	CL2
11	VSTRB
12	VCLK
13	VDIN
14	D_OFF
15	LED_ON

PIN2 FUNCTION:

NO	SYMBOL
1	VSS
2	VDD
3	NC
4	D0
5	D1
6	D2
7	D3
8	VFRAM
9	VM
10	CL1
11	CL2
12	NC
13	VSTRB
14	VCLK
15	VDIN
16	/D_OFF
17	VSS
18	LED_ON
19	VDD
20	VSS
21	21'
22	22'
23	23'
24	24'
25	25'
26	26'
27	27'
28	28'
29	29'
30	30'

 深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD					
DRAW NO.	CGG-240160A0FFB1WHR	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1	 2011-07-05	
TOLERANCE UNLESS:±0.2					