



DOTS SCALE:10/1

PINNO.	1	2	3	4	5	6	7	8	9	10
SIGNAL	CS1	CS2	GND	VDD	VO	RS	R/W	E	DB0	DB1
PINNO.	11	12	13	14	15	16	17	18	19	20
SIGNAL	DB2	DB3	DB4	DB5	DB6	DB7	RES	NC	BLA	BLK

- NOTES:
- 1.DISPLAY TYPE: FSTN
  - 2.VIEWING ANGLE: 6:00
  - 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
  - 4.OPERATING TEMP: -20°C ~ +70°C
  - 5.STORAGE TEMP: -30°C ~ +80°C
  - 6.LOGIC VOLTAGE: VDD=5.0V
  - 7.LCD DRIVER VOLTAGE: Vop=10.5V
  - 8.DRIVE METHOD: 1/64DUTY 1/9BIAS
  - 9.DRIVE IC: KS0107&KS0108
  - 10.BACKLIGHT TYPE: BLUE/WHITE EDGE LED



深圳市耀宇科技有限公司  
SHENZHEN YAO YU TECHNOLOGY CO., LTD

REV.	DESCRIPTION	DATE	DRAW NO.	YMFC12864G-1DPSPWD	DRAWN	ME CHECKED	EE CHECKED	APPROVED
			UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
				TOLERANCES UNLESS:±0.3				