


DETAIL FOR DOTS
SCALE 16:1

LCD TYPE	FSTN/POSITIVE/TRANSFLECTIVE
VIEW ANGLE	6:00
OPERATING TEMP	-10°C ~ +60°C
STORAGE TEMP	-20°C ~ +70°C
OPERATING VOLTAGE	3.0V
OPERATING CURRENT	-
LCD DRIVER VOLTAGE	9.0V
DRIVER METHOD	1/128 DUTY 1/9 BIAS
CONTROLLER IC	NT7532
BACKLIGHT COLOUR	WHITE
BACKLIGHT VOLTAGE	3.0V
BACKLIGHT CURRENT	30mA

PIN	1	2	3	4	5	6	7	8	9	10
DESC	CS1	RESETB	A0	/WR	/RD	DB0	DB1	DB2	DB3	DB4
PIN	11	12	13	14	15	16	17	18	19	20
DESC	DB5	DB6	DB7	VDD	VDD	VSS	VSS	VSS	LEDA	LEDK

 深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD				
DRAW NO. YM12864P-35	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1	
TOLERANCE UNLESS:±0.3				